PanReac AppliChem
ITW Reagents

Safety data sheet
according to UK REACH

Printing date 05.09.2025
Revision: 05.09.2025
Version number 6.03 (replaces version 6.02)

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

· **1.1 Product identifier**

· **Trade name: Silan-Sterol-1**

· **Article number:** 5650
· **Application of the substance / the mixture** Laboratory chemicals

· **1.3 Details of the supplier of the safety data sheet**
· **Manufacturer/Supplier:**
PANREAC QUIMICA S.L.U.
C/Garraf 2
Polígono Pla de la Bruguera
E-08211 Castellar del Vallès (Barcelona)
Tel. (+34) 937 489 400
Fax. (+34) 937 489 401
e-mail: product.safety@itwreagents.com

· **Further information obtainable from:** email: product.safety@panreac.com
· **1.4 Emergency telephone number:**
Single telephone number for emergency calls: 112 (EU)
Tel.: (+34) 937 489 499

SECTION 2: Hazards identification

· **2.1 Classification of the substance or mixture**
· **Classification according to Regulation (EC) No 1272/2008**

Flam. Liq. 2	H225 Highly flammable liquid and vapour.
Acute Tox. 4	H302 Harmful if swallowed.
Acute Tox. 3	H311 Toxic in contact with skin.
Acute Tox. 3	H331 Toxic if inhaled.
Skin Corr. 1A	H314 Causes severe skin burns and eye damage.
Eye Dam. 1	H318 Causes serious eye damage.

· **2.2 Label elements**
· **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the GB CLP regulation.

(Contd. on page 2)

Trade name: Silan-Sterol-1

(Contd. of page 1)

· **Hazard pictograms**

GHS02 GHS05 GHS06

· **Signal word** Danger

· **Hazard-determining components of labelling:**
pyridine
1,1,1,3,3,3-hexamethyldisilazane
chlorotrimethylsilane

· **Hazard statements**

H225	Highly flammable liquid and vapour.
H302	Harmful if swallowed.
H311+H331	Toxic in contact with skin or if inhaled.
H314	Causes severe skin burns and eye damage.

· **Precautionary statements**

P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER/doctor.
P321	Specific treatment (see on this label).
P361+P364	Take off immediately all contaminated clothing and wash it before reuse.
P405	Store locked up.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.

· **2.3 Other hazards**
· **Results of PBT and vPvB assessment**
· **PBT:** Not applicable.
· **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· **3.2 Mixtures**
· **Description:** Mixture of substances listed below with nonhazardous additions.

· **Dangerous components:**

CAS: 110-86-1 EINECS: 203-809-9 Reg.nr.: 01-2119493105-40-XXXX	pyridine Flam. Liq. 2, H225; Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332	>50-<100%
CAS: 999-97-3 EINECS: 213-668-5	1,1,1,3,3,3-hexamethyldisilazane Flam. Liq. 2, H225; Acute Tox. 3, H311; Acute Tox. 3, H331; Skin Corr. 1A, H314; Acute Tox. 4, H302	>15-≤20%
CAS: 75-77-4 EINECS: 200-900-5	chlorotrimethylsilane Flam. Liq. 2, H225; Skin Corr. 1A, H314; STOT SE 3, H335, EUH014	>5-≤10%

(Contd. on page 3)

Trade name: Silan-Sterol-1

(Contd. of page 2)

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· **4.1 Description of first aid measures**
· **General information:**
Immediately remove any clothing soiled by the product.
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
Remove breathing equipment only after contaminated clothing have been completely removed.
In case of irregular breathing or respiratory arrest provide artificial respiration.
Involve doctor immediately.
· **After inhalation:**
Supply fresh air or oxygen; call for doctor.
In case of unconsciousness place patient stably in side position for transportation.
If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
· **After skin contact:**
Call a doctor immediately.
Immediately wash with water and soap and rinse thoroughly.
Immediately remove any clothing soiled by the product.
· **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.
· **After swallowing:** Call a doctor immediately.
· **4.2 Most important symptoms and effects, both acute and delayed**
No further relevant information available.
· **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

*

SECTION 5: Firefighting measures

· **5.1 Extinguishing media**
· **Suitable extinguishing agents:**
CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
· **5.2 Special hazards arising from the substance or mixture**
In case of fire, the following can be released:
Nitrogen oxides (NOx)
Carbon monoxide and carbon dioxide
Forms explosive mixtures with air at ambient temperatures.
Vapours ara heavier than air and may spread along floors.
Beware of backfiring.
Forms explosive mixtures with air on intense heating.
· **5.3 Advice for firefighters**
· **Protective equipment:**
Mouth respiratory protective device.
Wear self-contained respiratory protective device.
Wear fully protective suit.
· **Additional information**
Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.
Contain escaping vapours with water.

(Contd. on page 4)

Trade name: Silan-Sterol-1

(Contd. of page 3)

SECTION 6: Accidental release measures

· **6.1 Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
Keep away from ignition sources.
Avoid substance contact.
Do not inhale steams/aerosols.
· **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
· **6.3 Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Use neutralising agent.
Dispose contaminated material as waste according to section 13.
Ensure adequate ventilation.
Clean up affected area.
· **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

*

SECTION 7: Handling and storage

· **7.1 Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
Prevent formation of aerosols.
Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).
· **Information about fire - and explosion protection:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Keep respiratory protective device available.

· **7.2 Conditions for safe storage, including any incompatibilities**
· **Storage:**
· **Requirements to be met by storerooms and receptacles:**
Store in a cool location.
Provide alkali-resistant floor.
· **Information about storage in one common storage facility:** Away from sources of ignition and heat.
· **Further information about storage conditions:**
Keep container tightly sealed.
Store in cool, dry conditions in well sealed receptacles.
Open receptacle only under localised extractor facilities.
Store receptacle in a well ventilated area.
Store only outside or in explosion proof rooms.
Store under lock and key and with access restricted to technical experts or their assistants only.
· **Recommended storage temperature:** Room Temperature
· **Storage class:** 3
· **7.3 Specific end use(s)** No further relevant information available.

(Contd. on page 5)

(Contd. of page 4)

*

SECTION 8: Exposure controls/personal protection

· **8.1 Control parameters**

· **Ingredients with limit values that require monitoring at the workplace:**	
110-86-1 pyridine	
WEL	Short-term value: 33 mg/m³, 10 ppm Long-term value: 16 mg/m³, 5 ppm

· **Additional information:** The lists valid during the making were used as basis.

· **8.2 Exposure controls**
· **Appropriate engineering controls** No further data; see section 7.
· **Individual protection measures, such as personal protective equipment**
· **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Store protective clothing separately.
Avoid contact with the eyes and skin.
· **Respiratory protection:**
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
Use suitable respiratory protective device only when aerosol or mist is formed.
· **Hand protection**

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
· **Material of gloves**
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
· **Penetration time of glove material**
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
· **For the permanent contact gloves made of the following materials are suitable:**
Recommended thickness of the material: ≥ 0.11 mm
Value for the permeation: Level ≥ 480 min
· **As protection from splashes gloves made of the following materials are suitable:**
Recommended thickness of the material: ≥ 0.11 mm
Value for the permeation: Level ≥ 480 min
· **Eye/face protection**

Gauze goggles

· **Body protection:**
Use protective suit.
Alkaline resistant protective clothing

(Contd. on page 6)

Trade name: Silan-Sterol-1

(Contd. of page 5)

Full head, face and neck protection
Flame retardant antistatic protective clothing

*

SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**	
· **General Information**	
· **Physical state**	Liquid
· **Colour:**	Not determined.
· **Odour:**	Characteristic
· **Odour threshold:**	Not determined.
· **Melting point/freezing point:**	Undetermined.
· **Boiling point or initial boiling point and boiling range**	57.3 °C (75-77-4 chlorotrimethylsilane)
· **Flammability**	Highly flammable.
· **Lower and upper explosion limit**	
· **Lower:**	1.7 Vol % (110-86-1 pyridine)
· **Upper:**	10.6 Vol % (110-86-1 pyridine)
· **Flash point:**	-18 °C (75-77-4 chlorotrimethylsilane)
· **Auto-ignition temperature:**	400 °C (75-77-4 chlorotrimethylsilane)
· **Decomposition temperature:**	Not determined.
· **pH at 20 °C**	>9
· **Viscosity:**	
· **Kinematic viscosity**	Not determined.
· **Dynamic:**	Not determined.
· **Solubility**	
· **water:**	Fully miscible.
· **Partition coefficient n-octanol/water (log value)**	Not determined.
· **Vapour pressure at 20 °C:**	20 hPa (110-86-1 pyridine)
· **Density and/or relative density**	
· **Density at 20 °C:**	0.94 g/cm³
· **Relative density**	Not determined.
· **Vapour density**	Not determined.

· **9.2 Other information**	
· **Appearance:**	
· **Form:**	Liquid
· **Important information on protection of health and environment, and on safety.**	
· **Ignition temperature:**	Product is not selfigniting.
· **Explosive properties:**	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· **Solvent content:**	
· **Solids content:**	0.0 %
· **Change in condition**	
· **Evaporation rate**	Not determined.

· **Information with regard to physical hazard classes**	
· **Explosives**	Void
· **Flammable gases**	Void
· **Aerosols**	Void
· **Oxidising gases**	Void

(Contd. on page 7)

(Contd. of page 6)

· **Gases under pressure**	Void
· **Flammable liquids**	Highly flammable liquid and vapour.
· **Flammable solids**	Void
· **Self-reactive substances and mixtures**	Void
· **Pyrophoric liquids**	Void
· **Pyrophoric solids**	Void
· **Self-heating substances and mixtures**	Void
· **Substances and mixtures, which emit flammable gases in contact with water**	Void
· **Oxidising liquids**	Void
· **Oxidising solids**	Void
· **Organic peroxides**	Void
· **Corrosive to metals**	Void
· **Desensitised explosives**	Void

SECTION 10: Stability and reactivity

· **10.1 Reactivity** No further relevant information available.
· **10.2 Chemical stability**
· **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
· **10.3 Possibility of hazardous reactions** No dangerous reactions known.
· **10.4 Conditions to avoid** No further relevant information available.
· **10.5 Incompatible materials:** No further relevant information available.
· **10.6 Hazardous decomposition products:** In the event of fire: See chapter 5

SECTION 11: Toxicological information

· **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
· **Acute toxicity**
Harmful if swallowed.
Toxic in contact with skin or if inhaled.
· **LD/LC50 values relevant for classification:**
Quantitative data on the toxicological effect of this product are not available.

· **Components**	**Type**	**Value**	**Species**
ATE (Acute Toxicity Estimates)			
Oral	LD50	950 mg/kg (rat)	
Dermal	LD50	992 mg/kg (rabbit)	
Inhalative	LC50/4 h	7.61 mg/l	
110-86-1 pyridine			
Oral	LD50	891 mg/kg (rat)	
Dermal	LD50	1,121 mg/kg (rabbit)	
Inhalative	LC50/4 h	11 mg/l (ATE)	
999-97-3 1,1,1,3,3,3-hexamethyldisilazane			
Oral	LD50	850 mg/kg (rat)	
Dermal	LD50	549.5 mg/kg (rabbit)	
Inhalative	LC50/4 h	3 mg/l (ATE)	

(Contd. on page 8)

Trade name: Silan-Sterol-1

(Contd. of page 7)

· **Primary irritant effect:**
· **Skin corrosion/irritation** Causes severe skin burns and eye damage.
· **Serious eye damage/irritation** Causes serious eye damage.
· **After inhalation:** Strong caustic effect on skin and mucous membranes.

· **Reproductive toxicity**	
999-97-3 1,1,1,3,3,3-hexamethyldisilazane	
NOAEL (Fertility)	8,700 mg/kg bw/day (rat)

· **11.2 Information on other hazards**

· **Endocrine disrupting properties**
None of the ingredients is listed.

SECTION 12: Ecological information

· **12.1 Toxicity**
· **Aquatic toxicity:** No further relevant information available.

· **Type of test**	**Effective concentration**	**Method**	**Assessment**
110-86-1 pyridine			
EC50	2,120 mg/l (Bakterien)		

· **12.2 Persistence and degradability** No further relevant information available.
· **12.3 Bioaccumulative potential** No further relevant information available.
· **12.4 Mobility in soil** No further relevant information available.
· **12.5 Results of PBT and vPvB assessment**
· **PBT:** Not applicable.
· **vPvB:** Not applicable.
· **12.6 Endocrine disrupting properties**
The product does not contain substances with endocrine disrupting properties.
· **12.7 Other adverse effects**
· **Additional ecological information:**
· **General notes:**
Do not allow product to reach ground water, water course or sewage system.
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Must not reach sewage water or drainage ditch undiluted or unneutralised.
Danger to drinking water if even small quantities leak into the ground.

SECTION 13: Disposal considerations

· **13.1 Waste treatment methods**
· **Recommendation**
Chemicals must be disposed of in compliance with the respective national regulations.
Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· **Uncleaned packaging:**
· **Recommendation:**
Disposal must be made according to official regulations.
Packagings that may not be cleansed are to be disposed of in the same manner as the product.

(Contd. on page 9)

Trade name: Silan-Sterol-1

(Contd. of page 8)

SECTION 14: Transport information

· **14.1 UN number or ID number**	
· **ADR, IMDG, IATA**	UN1993
· **14.2 UN proper shipping name**	
· **ADR, IMDG, IATA**	FLAMMABLE LIQUID, N.O.S. (PYRIDINE, Hexamethyldisilazane)
· **14.3 Transport hazard class(es)**	
· **ADR**	
· **Class**	3 (F1) Flammable liquids.
· **Label**	3
· **IMDG, IATA**	
· **Class**	3 Flammable liquids.
· **Label**	3
· **14.4 Packing group**	
· **ADR, IMDG, IATA**	II
· **14.5 Environmental hazards:**	Not applicable.
· **14.6 Special precautions for user**	Warning: Flammable liquids.
· **Hazard identification number (Kemler code):**	33
· **EMS Number:**	F-E,S-E
· **Stowage Category**	B
· **14.7 Maritime transport in bulk according to IMO instruments**	Not applicable.
· **Transport/Additional information:**	
· **ADR**	
· **Limited quantities (LQ)**	1L
· **Excepted quantities (EQ)**	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· **Transport category**	2
· **Tunnel restriction code**	D/E
· **IMDG**	
· **Limited quantities (LQ)**	1L
· **Excepted quantities (EQ)**	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml

(Contd. on page 10)

(Contd. of page 9)

· **UN "Model Regulation":** UN 1993 FLAMMABLE LIQUID, N.O.S. (PYRIDINE, HEXAMETHYLDISILAZANE), 3, II

SECTION 15: Regulatory information

· **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
· **Poisons Act**

· **Regulated explosives precursors**
None of the ingredients is listed.

· **Regulated poisons**
None of the ingredients is listed.

· **Reportable explosives precursors**
None of the ingredients is listed.

· **Reportable poisons**
None of the ingredients is listed.

· **Directive 2012/18/EU**
· **Named dangerous substances - ANNEX I** None of the ingredients is listed.
· **Seveso category**
H2 ACUTE TOXIC
P5c FLAMMABLE LIQUIDS
· **Qualifying quantity (tonnes) for the application of lower-tier requirements** 50 t
· **Qualifying quantity (tonnes) for the application of upper-tier requirements** 200 t
· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**
H225 Highly flammable liquid and vapour.
H302 Harmful if swallowed.
H311 Toxic in contact with skin.
H312 Harmful in contact with skin.
H314 Causes severe skin burns and eye damage.
H331 Toxic if inhaled.
H332 Harmful if inhaled.
H335 May cause respiratory irritation.
EUH014 Reacts violently with water.

· **Department issuing SDS:** Dept. Compliance
· **Abbreviations and acronyms:**
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic

(Contd. on page 11)

Trade name: Silan-Sterol-1

(Contd. of page 10)

vPvB: very Persistent and very Bioaccumulative
ATE: Acute toxicity estimate values
Flam. Liq. 2: Flammable liquids – Category 2
Acute Tox. 4: Acute toxicity – Category 4
Acute Tox. 3: Acute toxicity – Category 3
Skin Corr. 1A: Skin corrosion/irritation – Category 1A
Eye Dam. 1: Serious eye damage/eye irritation – Category 1
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
· *** Data compared to the previous version altered.**